

FOUNDATION

MISSION COLLECTION



WATERPROOF LUXURY VINYL PLANK FLOORING

The Foundation collection features four-sided painted bevels, realistic hardwood grain patterns and commercial-grade durability. Our luxury vinyl plank floors are simple to install and easy to maintain. The attached underlayment offers sound reduction making this collection the perfect choice for your home or office.



- PLANK DIMENSIONS:** 7" W x 48" L • 23.68 Sf/Ctn
- INSTALLATION:**
- Valinge 2G Locking- No adhesive necessary
 - Above • On • Below Grade
- CONSTRUCTION:**
- Rigid Core Technology • Thickness: 5.0 mm Overall
 - Wear Layer: 20 mil • Painted Bevel Edges & Sides
 - 1 mm attached EVA Acoustic Pad
 - High Performance High Wear Urethane Microceramic Top Coat
 - 15 Year Residential • 5 Year Light Commercial
- FINISH WARRANTIES:**
- MAINTENANCE:** Damp mop with a neutral floor cleaner followed by rinsing with clean water when floor has become too dirty for spot cleaning. See maintenance sheet for full instructions.

CERTIFICATIONS & TESTING RESULTS

Description	Standard	Symbol	Results
ASTM	D3261-17		Passes Requirement
Reaction to Fire	EN 13501-1 / ASTM 648		Bfl – s1 Classification Class I
Formaldehyde Emission	TSCA Title VI Compliant		Passes Requirement
VOC	FloorScore® GREENGUARD GOLD		Passes Requirement
Orthophthalates	US Consumer Product Safety Act 2008		Not Detected
Residual Indentation	ASTM F1914-07(2011)		Passes Requirement
Dimensional Stability	ASTM F2199-09(2014)		Passes Requirement
Resistance to Staining	ASTM F925		Passes Requirement
Dimensional Variance Straightness (s) Flatness (f) Height Difference (h) Squareness (q) Openings (o)	ISO 24337		Passes Requirement
Impact Resistance Big Ball Small Ball	NALFA LF 01-2011 / SECTION 3.5 / SECTION 3.6		No crack at 2600mm drop No crack at 750 mm drop
Static Load Resistance	ASTM F970-15		Residual Indentation: 0.02mm
Static Coefficient of Friction	ASTM D2047-11		Dry; 0.34
Color fastness to artificial light	ASTM F1515	N/A	ΔE < 8 after 300 hr
Heat Resistance	ASTM F1514-03 (2013)		Delta E = 0.66 Passes Requirements
Sound Attenuation	ASTM E 90 / ASTM E 492 - 6" drop ceiling		STC 60 / IIC 67
Abrasion	ASTM D4060-14	N/A	Passes Requirement
Castor Chair Resistance	NALFA LF 01-2011 Section 3.9	N/A	No Visible Damage, 25,000 rev

For additional information please visit
www.themissioncollection.com


A TRULY BEAUTIFUL FLOOR IS THE

FOUNDATION

TO ANY HOME OR OFFICE INTERIOR!



Floor Shown: River Silt



Distributed by B.R. Funsten & Co. and Tom Duffy Company



Golden Bark



Wheatfield



Shaded Canopy



Hearthstone



Sea Froth



Deep Canyon



Soft Suede



Winter Sky

- UNPARALLELED PERFORMANCE - PERFECT FOR FAMILIES, KIDS, AND PETS. IMPENETRABLE FROM WATER, SPILLS, ACCIDENTS, AND ODOR.

- CRAFTED TO STAND-UP TO A MODERN, ACTIVE LIFESTYLE. RESISTANT TO SCRATCHES, SCRAPES AND INDENTATIONS. STYLISH DESIGN, CONTINUOUS PATTERN RUN AND PAINTED BEVELS CREATE AN AUTHENTIC PLANK LOOK.

- EXTREME THERMAL STABILITY ALLOWS THE PRODUCT TO BE INSTALLED IN A WIDE RANGE OF TEMPERATURES, AND ON ANY LEVEL OF THE HOME.

- ATTACHED ACOUSTIC UNDERLAYMENT PROVIDES OPTIMAL CUSHIONING AND SOUND ABSORPTION.